

View Online at <https://aerobasegroup.com/nsn/5935-00-503-4095>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.340 inches

Overall Diameter:

1.510 inches

Environmental Protection:

Moisture resistant and salt water resistant and vibration resistant

Distance From Mounting Shoulder To Front Face:

0.778 inches

Mounting Facility Thickness:

0.125 inches

Threaded Device Type:

Back shell and mounting bushing

Mating End Quantity:

1

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

258.0 and 228.0 and 112.0 and 40.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Thready Qty Per Inch (tpi):

28 and 20

Thread Size:

0.875 inches and 1.000 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 1, class 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy 6061

Shell Surface Treatment:

Chromium

Shell Material Specification:

Qq-a-367, t6 federal specification single material response

Included Contact Quantity:

9 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.009 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Un and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.