# NSN 5935-00-503-5665

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-503-5665

# **Overall Length:**

Between 2.385 inches and 2.395 inches

#### **Overall Width:**

0.245 inches

#### **Environmental Protection:**

Moisture resistant and salt water resistant and vibration resistant

#### **Unthreaded Mounting Hole Diameter:**

Between 0.072 inches and 0.082 inches

#### **Distance Between Mounting Facility Centers:**

Between 2.245 inches and 2.255 inches

### **Mating End Quantity:**

1

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

#### **Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

#### **Polarization Method:**

Contact to contact polarizing keys

#### **Terminal Location:**

Back single mating end single contact grouping

# **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

#### **Insert Material:**

Plastic diallyl phthalate single mating end

# **Terminal Type:**

Pin single mating end single contact grouping

#### **Contact Material Specification:**

Qq-b-750, comp a federal specification single material response single mating end single contact grouping

# **Insert Material Specification:**

Mil-m-14, type sdg-f military specification single material response single mating end

# **Included Contact Quantity:**

40 single mating end single contact grouping

## **Included Contact Type:**

Hermaphrodite single mating end single contact grouping

# **Precious Material And Location:**

Contact surfaces gold

# **Precious Material And Weight:**

0.040 gold grains, troy

#### **Precious Material:**

Gold

# NSN 5935-00-503-5665

Electrical Receptacle Connector - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Mil-std (military Standard):

Mil-m-14 spec.