## NSN 5935-00-503-6168

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-503-6168 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.812 inches **Overall Diameter:** 0.688 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Bnc single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Shell Type:** Solid **Connector Locking Method:** Bayonet pin Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.500 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Silver single mating end single contact grouping **Insert Material:** Plastic single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Copper alloy **Shell Surface Treatment:** 

Nickel alloy

## NSN 5935-00-503-6168

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
1 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.005 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A039b0