NSN 5935-00-503-8494

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-503-8494

Body Style:

Straight shape, internal coupling

Overall Length:

1.104 inches

Overall Diameter:

1.766 inches

Environmental Protection:

Moisture resistant and vibration resistant and salt water resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

24-2 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0 and 100.0 and 128.0 and 228.0 and 265.0

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Operating Tempurature Rating:

Between -65.0 degrees celsius and 175.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Included Contact Quantity:

100 single mating end single contact grouping

NSN 5935-00-503-8494

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Plug Connector - Page 2 of 2



Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.100 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
96906-ms27473 government standard
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0