

View Online at <https://aerobasegroup.com/nsn/5935-00-503-8645>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape threaded

**Overall Length:**

Between 0.609 inches and 0.641 inches

**Overall Diameter:**

Between 0.328 inches and 0.359 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.234 inches and 0.250 inches

**Threaded Device Type:**

Mounting bushing

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

4 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

**Polarization Method:**

Contact

**Shell Type:**

Solid

**Connector Locking Method:**

Latch

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.375 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Insert Material:**

Plastic phenolic mineral filled single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Plastic

**Included Contact Quantity:**

4 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:**

0.004 gold grains, troy and 0.004 silver grains, troy

**Precious Material:**

Gold and silver

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0