NSN 5935-00-503-9103

Plastic tetrafluoroethylene single mating end

Thread Class:

Thread Direction:

2b

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-503-9103

Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
Between 0.479 inches and 0.489 inches
Overall Diameter:
0.375 inches
Environmental Protection:
Weatherproof
Cable Entrance Diameter:
Between 0.136 inches and 0.146 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
Sm single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
1000.0 single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling nut
Connector Cable Strain Relief Method:
Compression nut
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Thread Size:
0.312 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:

NSN 5935-00-503-9103

Electrical Plug Connector - Page 2 of 2



Terminal Type:
Solder well single mating end single contact grouping
Contact Material Specification:
Qq-c-530, comp ht federal specification single material response single mating end single contact grouping
Shell Material:
Copper alloy
Shell Surface Treatment:
Silver
Shell Surface Treatment Specification:
Qq-s-365, type 2, gr a federal specification single treatment response
Shell Material Specification:
Qq-b-626, comp 22, 1/2 h federal specification single material response
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial pin single mating end single contact grouping
Special Features:
Contact designation tm
Precious Material And Location:
Contact surface gold and shell surface silver
Precious Material And Weight:
0.005 gold grains, troy and 0.100 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0