NSN 5935-00-503-9267

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-503-9267

Body Style:
Straight type
Overall Length:
3.130 inches
Overall Height:
0.620 inches
Overall Width:
0.248 inches
Environmental Protection:
Heat resistant and cold resistant and vibration resistant and salt spray proof and shock resistant and moisture resistant and pressure proof
Unthreaded Mounting Hole Diameter:
0.098 inches
Distance Between Mounting Facility Centers:
2.840 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Mating end
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd
treatment response single mating end single contact grouping
Criticality Code Justification:
Feat
Terminal Type:

Contact Material Specification:

Tab, solder lug single mating end single contact grouping

Qq-c-533 federal specification single material response single mating end single contact grouping

NSN 5935-00-503-9267

Electrical Receptacle Connector - Page 2 of 2



Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response single mating end

Included Contact Quantity:

58 single mating end single contact grouping

Included Contact Type:

Square socket single mating end single contact grouping

Special Features:

Polarizing holes at positions 21 and 40

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.058 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.