

View Online at <https://aerobasegroup.com/nsn/5935-00-503-9285>

**Body Style:**

Straight type

**Overall Length:**

Between 4.249 inches and 4.261 inches

**Overall Height:**

0.620 inches

**Overall Width:**

0.248 inches

**Environmental Protection:**

Heat resistant and cold resistant and vibration resistant and salt spray proof and shock resistant and moisture resistant and pressure proof

**Unthreaded Mounting Hole Diameter:**

0.098 inches

**Distance Between Mounting Facility Centers:**

Between 3.960 inches and 3.970 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

**Polarization Method:**

Mating end

**Connector Locking Method:**

Friction

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping

**Criticality Code Justification:**

Feat

**Terminal Type:**

Tab, solder lug single mating end single contact grouping

**Contact Material Specification:**

Qq-c-533 federal specification single material response single mating end single contact grouping

**Insert Material Specification:**

Mil-m-14, ty sdg-f military specification single material response single mating end

**Included Contact Quantity:**

88 single mating end single contact grouping

**Included Contact Type:**

Square socket single mating end single contact grouping

**Special Features:**

Polarizing holes at contact positions 22 and 69

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.088 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.