

View Online at <https://aerobasegroup.com/nsn/5935-00-503-9644>

Thread Class:

2a and 2b and 2a

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Straight shape

Overall Length:

2.138 inches

Overall Height:

0.812 inches

Overall Width:

0.719 inches

Environmental Protection:

Moisture resistant and vibration resistant and salt water resistant

Distance Between Mounting Facility Centers:

Between 1.683 inches and 1.693 inches

Threaded Device Type:

Coupling facility and mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

34 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Jackscrew

Shell Type:

Solid

Connector Locking Method:

Jackscrew-socket

Thread Length:

0.320 inches

Thready Qty Per Inch (tpi):

32 and 32 and 40

Thread Size:

0.138 inches and 0.138 inches and 0.112 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 1, class 1 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Shell Surface Treatment Specification:

Mil-a-8625, type 1 military specification single treatment response

Shell Material Specification:

Qq-a-250/8, 0 federal specification single material response

Included Contact Quantity:

34 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

Polarized in a position

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.034 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-28748 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc and unc and unc

Specification Data:

81349-mil-c-28748-4 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.