NSN 5935-00-504-3081

Body Style:

Terminal Type:

Tab, solder lug single mating end single contact grouping

Hood, top opening, w/clamp

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-504-3081

Overall Length:
2.531 inches
Overall Height:
2.250 inches
Overall Width:
1.156 inches
Cable Entrance Diameter:
0.547 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
800.0 single mating end single contact grouping
Polarization Method:
Shell
Shell Type:
Hood, top opening
Connector Locking Method:
Latch
Connector Cable Strain Relief Method:
Cable clamp
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping

NSN 5935-00-504-3081Electrical Plug Connector - Page 2 of 2



Shell Material:
Copper alloy
Shell Surface Treatment:
Nickel
Insert Material Specification:
$\label{eq:mil-m-14} \mbox{Mil-m-14, ty sdg military specification single material response single mating end}$
Shell Guide Type And Location Designator:
A pin and f pin and 4 pin and 5 pin
Included Contact Quantity:
24 single mating end single contact grouping
Included Contact Type:
Leaf spring single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.024 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.