Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-504-4537

# Thread Class:

2a and 2a

# Thread Direction:

Right-hand and right-hand

# Body Style:

Straight shape, external coupling

#### **Overall Length:**

2.250 inches

#### **Overall Height:**

1.375 inches

#### **Overall Width:**

1.375 inches

#### Environmental Protection:

Fireproof and moisture resistant

#### **Unthreaded Mounting Hole Diameter:**

#### 0.177 inches

## Center To Center Distance Between Mounting Facilities Parallel To Height:

1.062 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.062 inches

## Distance From Mounting Shoulder To Front Face:

0.765 inches

## Threaded Device Type:

Coupling facility and hub

## Mating End Quantity:

1

# **Contact Position Arrangement Style:**

18-1 single mating end

## **Contact Removability:**

Removable single mating end all contact groupings

## **Contact Maximum Current Rating In Amps:**

22.0 single mating end all contact groupings

## Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end 1st contact grouping

## Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end 1st contact grouping

## **Polarization Method:**

Keyway or multiple keyway

## **Insert Position In Deg:**

0.0

#### Shell Type:

Solid



**Connector Locking Method:** Externally threaded shell **Thread Length:** 0.625 inches and 0.375 inches Thready Qty Per Inch (tpi): 18 and 20 **Thread Size:** 1.125 inches and 1.000 inches **Terminal Location:** Back single mating end all contact groupings **Contact Material:** Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Silver single mating end all contact groupings **Insert Material:** Plastic melamine single mating end **Terminal Type:** Crimp single mating end all contact groupings Shell Material: Steel **Shell Surface Treatment:** Cadmium and chromate **Included Contact Quantity:** 6 single mating end 2nd contact grouping **Included Contact Type:** Round socket single mating end all contact groupings **Precious Material And Location:** Contact surface silver **Precious Material:** Silver **Thread Series Designator:** Unef and unef Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A039b0