NSN 5935-00-506-4195

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-506-4195 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling w/strain relief **Body Length:** 2.312 inches **Overall Diameter:** 1.046 inches **Environmental Protection:** Moisture resistant and vibration resistant and salt water resistant **Cable Entrance Diameter:** 0.172 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 8s-1 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 **Shell Type:** Solid **Connector Locking Method:** Internally threaded coupling ring **Connector Cable Strain Relief Method:** Cable clamp Thread Length: 0.313 inches and 0.375 inches

Thread Size:

0.500 inches

NSN 5935-00-506-4195

Electrical Plug Connector - Page 2 of 2



Terminal Location:
Back single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Test Data Document:
81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef
Specification Data:
81349-mil-c-5015 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0