Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-506-5510

Body Style:

Angle, shape, internal coupling

Overall Length:

1.531 inches

Overall Height:

2.375 inches

Overall Diameter:

Between 0.790 inches and 0.860 inches

Environmental Protection:

Shock proof and vibration resistant

Mating End Quantity:

1

Contact Position Arrangement Style:

N single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

120.0 and 240.0

Shell Type:

Solid

Connector Locking Method:

Spring friction

Connector Cable Strain Relief Method:

Shrinkable tubing

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic polychlorotrifluoroethylene single mating end

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-c-530, h federal specification single material response single mating end single contact grouping

Shell Material:

Steel comp 303

NSN 5935-00-506-5510

Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment: Passivate **Shell Material Specification:** Qq-s-764, cond a federal specification single material response Included Contact Quantity: 1 single mating end single contact grouping Included Contact Type: Coaxial pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.005 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0