NSN 5935-00-506-6449

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-506-6449

Body Style:
Straight shape
Overall Length:
1.485 inches
Overall Height:
0.468 inches
Overall Width:
0.305 inches
Unthreaded Mounting Hole Diameter:
Between 0.088 inches and 0.094 inches
Distance Between Mounting Facility Centers:
Between 1.260 inches and 1.270 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
37 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, class 2 federal specification single treatment response
Insert Material Specification:
Mil-p-19833, type gdi-30 military specification single material response single mating end

Included Contact Quantity:

37 single mating end single contact grouping

NSN 5935-00-506-6449

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.037 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0

Mil-std (military Standard):

Mil-p-19833 spec.