NSN 5935-00-506-6775

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-506-6775 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Angle shape, external coupling **Overall Length:** 1.500 inches **Overall Height:** 1.625 inches **Distance From Mounting Shoulder To Front Face:** 0.750 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Bnc single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Bayonet pin **Connector Cable Strain Relief Method:** Crimp type Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.375 inches **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Surface Treatment:** Gold

Included Contact Quantity:

1 single mating end single contact grouping

NSN 5935-00-506-6775

Electrical Receptacle Connector - Page 2 of 2



Bushing Accommodation Hole Shape:
Round w/flat
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces and shell surface gold
Precious Material And Weight:
0.105 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0