## NSN 5935-00-506-6856

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-506-6856

view Online at https://aerobasegroup.com/hsh/5555-00-500-6050
Overall Length:
2.000 inches
Diameter:
2.062 inches
Mounting Hole Circle Radius:
1.250 inches
Overall Diameter:
2.875 inches
Unthreaded Mounting Hole Diameter:
0.187 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
3 single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
30.0 single mating end all contact groupings
Contact Maximum Ac Voltage Rating In Volts:
250.0 single mating end all contact groupings
Contact Maximum Dc Voltage Rating In Volts:
250.0 single mating end all contact groupings
Polarization Method:
Contact
Shell Type:
Solid
Connector Locking Method:
Contact twistlock
Terminal Location:
Side single mating end all contact groupings
Insert Material:
Plastic phenolic single mating end
Terminal Type:
Screw single mating end all contact groupings
Shell Material:
Copper alloy
Insert Material Specification:
Mil-m-14, type cfg military specification single material response single mating end
Included Contact Quantity:

2 single mating end 2nd contact grouping

**Included Contact Type:** 

Curved pin w/inside lip single mating end 1st contact grouping

## NSN 5935-00-506-6856

Electrical Receptacle Connector - Page 2 of 2



N/a
Unit Of Measure:
Demilitarization:
No
INO
Fiig:

Mil-std (military Standard):

Mil-m-14 spec.

Shelf Life: