

View Online at https://aerobasegroup.com/nsn/5935-00-506-7421

| Tł | nread Class: |
|----|---|
| 2a | a and 2b |
| Tł | nread Direction: |
| Ri | ght-hand |
| B | ody Style: |
| St | raight shape w/screw locks |
| 0 | verall Length: |
| 1. | 484 inches |
| 0 | verall Height: |
| 0. | 590 inches |
| 0 | verall Width: |
| 0. | 390 inches |
| Eı | nvironmental Protection: |
| Vi | bration resistant |
| Tł | nreaded Device Type: |
| C | oupling facility |
| Μ | ating End Quantity: |
| 1 | |
| C | ontact Position Arrangement Style: |
| 44 | single mating end |
| Pe | olarization Method: |
| Ja | ackscrew |
| Tł | nready Qty Per Inch (tpi): |
| 48 | 3 |
| Tł | nread Size: |
| 0. | 099 inches |
| In | sert Material: |
| ΡI | astic diallyl phthalate single mating end |
| In | sert Material Specification: |
| Μ | il-m-14, ty sdg-f military specification single material response single mating end |
| Tł | nread Series Designator: |
| U | nc |
| SI | nelf Life: |
| N/ | /a |
| U | nit Of Measure: |
| | |
| D | emilitarization: |
| N | o |
| Fi | ig: |
| A | 039b0 |
| Μ | il-std (military Standard): |
| | |