## NSN 5935-00-506-7430

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-506-7430

**Thread Class:** 

2a and 2b and 2a

**Thread Direction:** 

Right-hand and right-hand and right-hand

**Body Style:** 

Straight shape

**Overall Length:** 

Between 1.474 inches and 1.494 inches

**Overall Height:** 

Between 0.636 inches and 0.650 inches

**Overall Width:** 

0.410 inches

**Environmental Protection:** 

Vibration resistant

**Distance Between Mounting Facility Centers:** 

Between 1.264 inches and 1.270 inches

**Threaded Device Type:** 

Coupling facility and mounting stud

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

44 single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

5.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

250.0 single mating end single contact grouping

**Polarization Method:** 

Jackscrew

**Connector Locking Method:** 

Jackscrew-socket

Thready Qty Per Inch (tpi):

48 and 48 and 56

**Thread Size:** 

0.099 inches and 0.099 inches and 0.086 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold and copper single mating end single contact grouping

## NSN 5935-00-506-7430

Mil-m-14 spec.

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Contact Material Specification:
Qq-b-750 federal specification single material response single mating end single contact grouping
Insert Material Specification:
Mil-m-14, type sdg-f military specification single material response single mating end
Included Contact Quantity:
44 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Furnished items - potting boot
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.044 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc and unc and unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):