# NSN 5935-00-509-4557

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-509-4557

| Body Style:  |
|--|
| Straight type  |
| Overall Length:  |
| 2.380 inches   |
| Overall Height:  |
| 0.620 inches   |
| Overall Width:   |
| 0.248 inches   |
| Environmental Protection:  |
| Heat resistant and cold resistant and vibration resistant and salt spray proof and shock resistant and moisture resistant and pressure proof |
| Unthreaded Mounting Hole Diameter:   |
| 0.098 inches   |
| Distance Between Mounting Facility Centers:  |
| 2.090 inches   |
| Mating End Quantity:   |
| 1  |
| Contact Position Arrangement Style:  |
| 2 rows of contacts non-inserted board single mating end  |
| Contact Removability:  |
| Nonremovable single mating end single contact grouping   |
| Contact Maximum Current Rating In Amps:  |
| 3.0 single mating end single contact grouping  |
| Polarization Method:   |
| Mating end   |
| Connector Locking Method:  |
| Friction   |
| Terminal Location:   |
| Back single mating end single contact grouping   |
| Contact Material:  |
| Copper alloy single mating end single contact grouping   |
| Contact Surface Treatment:   |
| Gold single mating end single contact grouping   |
| Insert Material:   |
| Plastic diallyl phthalate single mating end  |
| Contact Surface Treatment Specification:   |
| Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd   |
| treatment response single mating end single contact grouping   |
| Criticality Code Justification:  |
| Feat   |
| Terminal Type:   |

## **Contact Material Specification:**

Solder well single mating end single contact grouping

Qq-c-533 federal specification single material response single mating end single contact grouping

# NSN 5935-00-509-4557

Electrical Receptacle Connector - Page 2 of 2



#### **Insert Material Specification:**

Mil-m-14 military specification 1st material response single mating end or mil-p-19833 military specification 2nd material response single mating end

### **Included Contact Quantity:**

38 single mating end single contact grouping

### **Included Contact Type:**

Square socket single mating end single contact grouping

#### **Special Features:**

Polarized at positions 17 and 24

#### **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.040 gold grains, troy

#### **Precious Material:**

Gold

#### Shelf Life:

N/a

#### **Unit Of Measure:**

### Demilitarization:

No

### Fiig:

A039b0

### Mil-std (military Standard):

Mil-g-45204 spec.