## NSN 5935-00-513-2102

Electrical Receptacle Connector - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5935-00-513-2102               |
|---|
| Body Style:   |
| Straight shape w/cover  |
| Overall Length:   |
| 3.500 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Length:   |
| 2.875 inches  |
| Overall Height:   |
| 2.281 inches  |
| Overall Width:  |
| 3.500 inches  |
| Unthreaded Mounting Hole Diameter:  |
| 0.281 inches  |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 0.875 inches  |
| Threaded Device Type:   |
| Coupling facility   |
| Mating End Quantity:  |
| 1   |
| Contact Removability:   |
| Nonremovable single mating end single contact grouping                      |
| Contact Maximum Current Rating In Amps:                                     |
| 35.0 single mating end single contact grouping                              |
| Contact Maximum Ac Voltage Rating In Volts:                                 |
| 700.0 single mating end single contact grouping                             |
| Polarization Method:  |
| Contact   |
| Shell Type:   |
| Solid   |
| Connector Locking Method:   |
| Externally threaded shell   |
| Terminal Location:  |
| Back single mating end single contact grouping                              |
| Terminal Type:  |
| Solder well single mating end single contact grouping                       |
| Shell Surface Treatment:  |
| Cadmium and chromate  |
| Included Contact Quantity:  |
| 28 single mating end single contact grouping                                |
| Included Contact Type:  |
| Round socket single mating end single contact grouping                      |
| Shelf Life:   |

N/a

## NSN 5935-00-513-2102

Electrical Receptacle Connector - Page 2 of 2



|   | 1  | :. | ~  | 84  |    |    |      |   |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A039b0