Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-513-2668

## Thread Class:

2a

**Thread Direction:** 

Right-hand

#### **Body Style:**

Straight shape

### **Overall Length:**

Between 2.895 inches and 2.905 inches

### **Overall Height:**

0.800 inches

**Overall Width:** 

Between 0.355 inches and 0.365 inches

### **Distance Between Mounting Facility Centers:**

Between 2.595 inches and 2.605 inches

## Threaded Device Type:

Mounting stud

## Mating End Quantity:

1

# **Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

### Contact Removability:

Nonremovable single mating end single contact grouping

# **Polarization Method:**

Guide pin/socket

## Thread Length:

0.250 inches

# Thread Size:

0.112 inches

### **Terminal Location:**

Side single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping

### **Insert Material:**

Plastic diallyl phthalate single mating end

### **Terminal Type:**

Pin single mating end single contact grouping

# **Included Contact Quantity:**

23 single mating end single contact grouping

### Included Contact Type:

Round pin single mating end single contact grouping



**Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.023 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No

---

Fiig:

A039b0