NSN 5935-00-513-5001

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-513-5001
Body Style:
Straight shape, internal coupling w/strain relief
Body Length:
1.812 inches
Overall Diameter:
1.265 inches
Environmental Protection:
Moisture resistant

Between 0.475 inches and 0.510 inches

Cable Entrance Diameter:

Mating End Quantity:

Contact Position Arrangement Style:

16-8 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

900.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

1250.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

118.0

Shell Type:

Solid

Connector Locking Method:

Bayonet latch

Connector Cable Strain Relief Method:

Cable clamp

Operating Tempurature Rating:

Between -65.0 degrees celsius and 200.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic epoxy single mating end and glass fiber single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

NSN 5935-00-513-5001Electrical Plug Connector - Page 2 of 2



Crimp single mating end single contact grouping Shell Material: Aluminum alloy Shell Surface Treatment: Cadmium and nickel Shell Surface Treatment Specification: Qq-p-416 federal specification 1st treatment response and qq-n-290, class 2 federal specification 2nd treatment response Included Contact Quantity: 8 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Precious Material And Location: Contact surfaces gold
Aluminum alloy Shell Surface Treatment: Cadmium and nickel Shell Surface Treatment Specification: Qq-p-416 federal specification 1st treatment response and qq-n-290, class 2 federal specification 2nd treatment response Included Contact Quantity: 8 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Precious Material And Location:
Shell Surface Treatment: Cadmium and nickel Shell Surface Treatment Specification: Qq-p-416 federal specification 1st treatment response and qq-n-290, class 2 federal specification 2nd treatment response Included Contact Quantity: 8 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Precious Material And Location:
Cadmium and nickel Shell Surface Treatment Specification: Qq-p-416 federal specification 1st treatment response and qq-n-290, class 2 federal specification 2nd treatment response Included Contact Quantity: 8 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Precious Material And Location:
Shell Surface Treatment Specification: Qq-p-416 federal specification 1st treatment response and qq-n-290, class 2 federal specification 2nd treatment response Included Contact Quantity: 8 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Precious Material And Location:
Qq-p-416 federal specification 1st treatment response and qq-n-290, class 2 federal specification 2nd treatment response Included Contact Quantity: 8 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Precious Material And Location:
Included Contact Quantity: 8 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Precious Material And Location:
8 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping Precious Material And Location:
Included Contact Type: Round pin single mating end single contact grouping Precious Material And Location:
Round pin single mating end single contact grouping Precious Material And Location:
Precious Material And Location:
Contact surfaces gold
Contact surfaces gold
Precious Material And Weight:
0.008 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.