

View Online at <https://aerobasegroup.com/nsn/5935-00-513-5001>

**Body Style:**

Straight shape, internal coupling w/strain relief

**Body Length:**

1.812 inches

**Overall Diameter:**

1.265 inches

**Environmental Protection:**

Moisture resistant

**Cable Entrance Diameter:**

Between 0.475 inches and 0.510 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

16-8 single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

900.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

1250.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

118.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet latch

**Connector Cable Strain Relief Method:**

Cable clamp

**Operating Temperature Rating:**

Between -65.0 degrees celsius and 200.0 degrees celsius

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic epoxy single mating end and glass fiber single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and nickel

**Shell Surface Treatment Specification:**

Qq-p-416 federal specification 1st treatment response and qq-n-290, class 2 federal specification 2nd treatment response

**Included Contact Quantity:**

8 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.008 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.