Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-517-9638

# **Body Style:** Straight shape, external coupling **Overall Length:** 0.838 inches **Overall Height:** Between 1.015 inches and 1.047 inches **Overall Width:** Between 1.015 inches and 1.047 inches **Environmental Protection:** Moisture proof and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.802 inches and 0.822 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.802 inches and 0.822 inches **Distance From Mounting Shoulder To Front Face:** 0.432 inches Mating End Quantity: 1 **Contact Position Arrangement Style:** 12-10 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 60.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Nickel alloy single mating end single contact grouping **Contact Surface Treatment:** Tin single mating end single contact grouping

# NSN 5935-00-517-9638

Electrical Receptacle Connector - Page 2 of 2



## Insert Material:

Glass single mating end

# **Terminal Type:**

Solder well single mating end single contact grouping

## Shell Material:

Steel

# Shell Surface Treatment:

Tin

# Included Contact Quantity:

10 single mating end single contact grouping

# Included Contact Type:

Round pin single mating end single contact grouping

Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A039b0