

View Online at <https://aerobasegroup.com/nsn/5935-00-518-2077>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.060 inches

Overall Diameter:

Between 0.745 inches and 0.755 inches

Distance From Mounting Shoulder To Front Face:

Between 0.785 inches and 0.795 inches

Threaded Device Type:

Mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

120.0 and 240.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Connector Cable Strain Relief Method:

Crimp type

Thread Size:

0.437 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper single mating end single contact grouping

Insert Material:

Plastic tetrafluoroethylene single mating end

Terminal Type:

Solder well single mating end single contact grouping

Contact Material Specification:

Qq-c-530, condition h federal specification single material response single mating end single contact grouping

Shell Material:

Copper alloy

Shell Material Specification:

Qq-b-626, comp 22 federal specification single material response

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/double flat

Included Contact Type:

Coaxial pin single mating end single contact grouping

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0