

View Online at <https://aerobasegroup.com/nsn/5935-00-518-6361>

Thread Class:

2a

Thread Direction:

Right-hand

Environmental Protection:

Vibration resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

10sl-4 single mating end

Contact Removability:

Nonremovable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

10.0 single mating end all contact groupings

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thread Length:

0.438 inches

Thready Qty Per Inch (tpi):

24

Thread Size:

0.625 inches

Terminal Location:

Back single mating end all contact groupings

Contact Surface Treatment:

Cadmium single mating end all contact groupings and tin single mating end all contact groupings

Insert Material:

Plastic single mating end

Terminal Type:

Tab, solder lug single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and tin

Included Contact Quantity:

12 single mating end 1st contact grouping

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0