

View Online at <https://aerobasegroup.com/nsn/5935-00-518-6361>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Environmental Protection:**

Vibration resistant

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

10sl-4 single mating end

**Contact Removability:**

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

10.0 single mating end all contact groupings

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Thread Length:**

0.438 inches

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.625 inches

**Terminal Location:**

Back single mating end all contact groupings

**Contact Surface Treatment:**

Cadmium single mating end all contact groupings and tin single mating end all contact groupings

**Insert Material:**

Plastic single mating end

**Terminal Type:**

Tab, solder lug single mating end all contact groupings

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and tin

**Included Contact Quantity:**

12 single mating end 1st contact grouping

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0