## NSN 5935-00-518-7068

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-518-7068 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Angle shape, external coupling **Overall Length:** 1.500 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 0.719 inches **Overall Height:** 1.500 inches **Overall Width:** 1.000 inches **Unthreaded Mounting Hole Diameter:** 0.125 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.719 inches **Distance From Mounting Shoulder To Rear Face:** 0.406 inches Flange Length: 1.000 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.750 inches **Terminal Location:** Side single mating end single contact grouping **Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Silver single mating end single contact grouping

## NSN 5935-00-518-7068

**Insert Material:** 

Electrical Receptacle Connector - Page 2 of 2



Plastic single mating end
Contact Surface Treatment Specification:
Qq-s-365 federal specification single treatment response single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Copper alloy
Shell Surface Treatment:
Silver
Shell Surface Treatment Specification:
Qq-s-365 federal specification single treatment response
Included Contact Quantity:
2 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact and shell surfaces silver
Precious Material And Weight:
0.110 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0