## NSN 5935-00-518-8967

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-518-8967 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling w/ground **Body Length:** 2.188 inches **Overall Diameter:** 1.969 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 28-12 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 22.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 90.0 Shell Type: Split **Connector Locking Method:** Internally threaded coupling nut **Connector Cable Strain Relief Method:** Potting type Thready Qty Per Inch (tpi): 18 **Thread Size:** 

1.750 inches

**Terminal Location:** 

Back single mating end single contact grouping

## NSN 5935-00-518-8967

Electrical Plug Connector - Page 2 of 2



Contact Surface	Treatment:		

Gold single mating end single contact grouping and silver single mating end single contact grouping

**Terminal Type:** 

Solder well single mating end single contact grouping

**Shell Material:** 

Aluminum alloy

**Shell Surface Treatment:** 

Cadmium

**Included Contact Quantity:** 

26 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

**Precious Material And Location:** 

Contact surface gold and contact surface silver

**Precious Material And Weight:** 

0.026 gold grains, troy and 0.026 silver grains, troy

**Precious Material:** 

Gold and silver

## **Test Data Document:**

81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-c-5015 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0