

View Online at <https://aerobasegroup.com/nsn/5935-00-520-1334>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external/internal coupling

**Overall Length:**

1.500 inches

**Overall Diameter:**

0.750 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

Tnc 2nd mating end

**Contact Removability:**

Nonremovable all mating ends single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet latch and externally threaded shell

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 all mating ends single contact grouping

**Thready Qty Per Inch (tpi):**

20

**Thread Size:**

0.750 inches

**Contact Material:**

Copper alloy all mating ends single contact grouping

**Contact Surface Treatment:**

Gold all mating ends single contact grouping

**Insert Material:**

Plastic all mating ends

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response all mating ends single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Included Contact Quantity:**

1 all mating ends single contact grouping

**Included Contact Type:**

Coaxial socket 1st mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.005 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.