AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-00-520-8560

Thread Class:
2a and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.430 inches
Overall Height:
Between 1.338 inches and 1.348 inches
Overall Width:
Between 1.338 inches and 1.348 inches
Environmental Protection:
Moisture resistant and vibration resistant and salt water resistant
Unthreaded Mounting Hole Diameter:
Between 0.116 inches and 0.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 1.057 inches and 1.067 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.057 inches and 1.067 inches
Distance From Mounting Shoulder To Front Face:
Between 0.708 inches and 0.728 inches
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
18-31 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thread Length:
0.290 inches and 0.281 inches
Thready Qty Per Inch (tpi):
18 and 18

## NSN 5935-00-520-8560

Electrical Receptacle Connector - Page 2 of 2



**Thread Size:** 1.063 inches and 1.188 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic single mating end **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Aluminum alloy 6061 **Shell Surface Treatment:** Anodize **Shell Surface Treatment Specification:** Mil-a-8625 military specification single treatment response **Shell Material Specification:** Qq-a-367, comp 6061, t6 federal specification single material response **Included Contact Quantity:** 31 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.031 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unef and unef Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-a-8625 spec.