Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-520-8581

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling w/backshell
Overall Height:
1.250 inches
Overall Width:
1.250 inches
Environmental Protection:
Fireproof and moisture resistant and vibration resistant and salt water resistant
Unthreaded Mounting Hole Diameter:
Between 0.116 inches and 0.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.969 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.969 inches
Distance From Mounting Shoulder To Front Face:
0.718 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
24 number 20 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
18
Thread Size:
1.063 inches
Terminal Location:
Back single mating end single contact grouping



Copper allov si	ngle mating end single contact grouping
	ce Treatment:
Rhodium single	e mating end single contact grouping
nsert Material	
Rubber synthet	ic single mating end
Terminal Type	<u>.</u>
Crimp single m	ating end single contact grouping
Shell Material:	
Stainless steel	
Insert Material	Specification:
Mil-r-5847, clas	s 2 military specification single material response single mating end
Included Cont	act Quantity:
24 single matin	g end single contact grouping
Included Cont	act Type:
Round pin sing	le mating end single contact grouping
Precious Mate	rial And Location:
Contact surface	es rhodium
Precious Mate	rial And Weight:
0.024 rhodium	grains, troy
Precious Mate	rial:
Rhodium	
Thread Series	Designator:
Unef	
Shelf Life:	
N/a	
Unit Of Measu	re:
Demilitarizatio	on:
No	
Fiig:	
A039b0	
	ry Standard):