Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-520-8674

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling w/backshell
Overall Height:
1.125 inches
Overall Width:
1.125 inches
Environmental Protection:
Fireproof and moisture resistant and vibration resistant and salt water resistant
Unthreaded Mounting Hole Diameter:
Between 0.116 inches and 0.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.906 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.906 inches
Distance From Mounting Shoulder To Front Face:
0.718 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
14-15 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thready Qty Per Inch (tpi):
20
Thread Size:
0.938 inches
Terminal Location:
Back single mating end single contact grouping



Conner allow	single mating end single contact grouping
	face Treatment:
	gle mating end single contact grouping
Insert Mater	
	hetic single mating end
Terminal Ty	
-	mating end single contact grouping
Shell Materi	
Stainless ste	el
Insert Mater	rial Specification:
Mil-r-5847, c	lass 2 military specification single material response single mating end
ncluded Co	ontact Quantity:
15 single ma	ating end single contact grouping
ncluded Co	ontact Type:
Round pin si	ingle mating end single contact grouping
Precious Ma	aterial And Location:
Contact surfa	aces rhodium
Precious Ma	aterial And Weight:
0.015 rhodiu	m grains, troy
Precious Ma	aterial:
Rhodium	
Thread Seri	es Designator:
Unef	
Shelf Life:	
N/a	
Unit Of Mea	sure:
Demilitariza	ition:
No	
Fiig:	
A039b0	
Mil-std (mili	itary Standard): Dec.