## NSN 5935-00-520-8729

Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-00-520-8729

**Thread Class:** 

2a and 2a

**Thread Direction:** 

Right-hand and right-hand

**Body Style:** 

Straight shape, external coupling

**Overall Length:** 

1.430 inches

**Overall Height:** 

Between 1.026 inches and 1.036 inches

**Overall Width:** 

Between 1.026 inches and 1.036 inches

**Environmental Protection:** 

Moisture resistant and vibration resistant and salt water resistant

**Unthreaded Mounting Hole Diameter:** 

Between 0.116 inches and 0.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.807 inches and 0.812 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.807 inches and 0.817 inches

**Distance From Mounting Shoulder To Front Face:** 

Between 0.708 inches and 0.728 inches

**Threaded Device Type:** 

Back shell and coupling facility

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

12-p single mating end

Contact Removability:

Removable single mating end single contact grouping

**Polarization Method:** 

Key, multiple key groove

**Insert Position In Deg:** 

342.0 and 211.0 and 168.0 and 101.0

Shell Type:

Solid

**Connector Locking Method:** 

Externally threaded shell

**End Application:** 

Engine, aircraft tf-34

Thread Length:

0.290 inches and 0.281 inches

## NSN 5935-00-520-8729

Electrical Receptacle Connector - Page 2 of 3



The 1 Co Political (12)
Thready Qty Per Inch (tpi):
20 and 20
Thread Size:
0.750 inches and 0.875 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic single mating end
Criticality Code Justification:
Feat
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy 6061
Shell Surface Treatment:
Anodize
Shell Surface Treatment Specification:
Mil-a-8625 military specification single treatment response
Shell Material Specification:
Qq-a-367, comp 6061, t6 federal specification single material response
Included Contact Quantity:
12 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Weapon system essential
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.012 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 5935-00-520-8729

Electrical Receptacle Connector - Page 3 of 3



Fiig:

A039b0

Mil-std (military Standard):

Mil-a-8625 spec.