

View Online at <https://aerobasegroup.com/nsn/5935-00-520-9380>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape

Overall Length:

1.411 inches

Overall Height:

Between 3.095 inches and 3.125 inches

Overall Width:

Between 1.985 inches and 2.015 inches

Environmental Protection:

Moisture resistant and shock resistant and vibration resistant

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 2.778 inches and 2.788 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.432 inches and 1.442 inches

Distance From Mounting Shoulder To Front Face:

0.490 inches

Threaded Device Type:

Mounting hole

Mating End Quantity:

2

Contact Position Arrangement Style:

67 1st mating end

Contact Removability:

Removable all mating ends all contact groupings

Contact Maximum Current Rating In Amps:

7.5 1st mating end 2nd contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 1st mating end all contact groupings

Shell Type:

Solid

Thread Size:

0.112 inches

Terminal Location:

Back all mating ends all contact groupings

Contact Material:

Nickel alloy 2nd mating end all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings and copper all mating ends all contact groupings

Insert Material:

Plastic epoxy 2nd mating end

Terminal Type:

Crimp all mating ends all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Shell Material Specification:

Qq-a-591 federal specification single material response

Insert Material Specification:

Mil-m-19833, type gdi-30f military specification single material response 1st mating end

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.175 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.