Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-520-9446

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
Between 1.406 inches and 1.471 inches
Overall Height:
Between 1.117 inches and 1.133 inches
Overall Width:
Between 1.117 inches and 1.133 inches
Environmental Protection:
Moisture resistant and pressure proof and vibration resistant
Unthreaded Mounting Hole Diameter:
Between 0.116 inches and 0.126 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 0.901 inches and 0.911 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 0.901 inches and 0.911 inches
Distance From Mounting Shoulder To Front Face:
Between 0.894 inches and 0.906 inches
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
14-19 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Thready Qty Per Inch (tpi):
28
Thread Size:
0.875 inches

Electrical Receptacle Connector - Page 2 of 2



Terminal Location:	
Back single mating er	nd single contact grouping
Contact Material:	
Copper alloy single m	ating end single contact grouping
Contact Surface Tre	atment:
Gold single mating en	d single contact grouping
Contact Surface Tre	atment Specification:
Mil-g-45204, type 1, c	lass 1 military specification single treatment response single mating end single contact grouping
Terminal Type:	
Crimp single mating e	nd single contact grouping
Shell Material:	
Aluminum alloy 6061	
Shell Surface Treatn	nent:
Cadmium	
Shell Surface Treatn	nent Specification:
Qq-p-416, type 2, cl 3	3 federal specification single treatment response
Shell Material Specif	ication:
Qq-a-367, comp 6061	, t6 federal specification single material response
Included Contact Qu	antity:
19 single mating end	single contact grouping
Included Contact Ty	pe:
Round socket single r	nating end single contact grouping
Precious Material An	nd Location:
Contact surfaces gold	
Precious Material An	nd Weight:
0.019 gold grains, tro	у
Precious Material:	
Gold	
Test Data Document	:
81349-mil-c-81511 sp	ecification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes com	mercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and pe	rformance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Desig	nator:
Un	
Specification Data:	
81349-mil-c-81511/21	government specification
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military Star	ndard):
<u></u>	