

View Online at <https://aerobasegroup.com/nsn/5935-00-521-1325>

**Thread Class:**

2b

**Body Style:**

Straight shape, flush mount

**Overall Length:**

1.226 inches

**Overall Height:**

Between 3.060 inches and 3.090 inches

**Overall Width:**

Between 1.985 inches and 2.015 inches

**Environmental Protection:**

Moisture resistant and shock resistant and vibration resistant

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

Between 2.778 inches and 2.788 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 1.432 inches and 1.442 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.055 inches and 0.065 inches

**Threaded Device Type:**

Mounting hole

**Mating End Quantity:**

2

**Contact Removability:**

Removable all mating ends all contact groupings

**Contact Maximum Current Rating In Amps:**

7.5 1st mating end 3rd contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 1st mating end 1st contact grouping

**Polarization Method:**

1 polarization post

**Shell Type:**

Solid

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 all mating ends all contact groupings

**Thread Size:**

0.112 inches

**Terminal Location:**

Back all mating ends all contact groupings

**Contact Material:**

Copper alloy all mating ends all contact groupings

**Contact Surface Treatment:**

Gold all mating ends all contact groupings and copper all mating ends all contact groupings

**Insert Material:**

Plastic epoxy single mating end and glass single mating end

**Terminal Type:**

Crimp all mating ends all contact groupings

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and chromate

**Insert Material Specification:**

Mil-p-19833, type gdi-30f military specification single material response 2nd mating end

**Precious Material And Location:**

Contact surface gold

**Precious Material And Weight:**

0.138 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-p-19833 spec.