## NSN 5935-00-521-2388

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-521-2388

**Body Style:** 

Straight shape, internal coupling w/strain relief

**Body Length:** 

1.310 inches

**Overall Diameter:** 

1.156 inches

**Environmental Protection:** 

Moisture resistant and vibration resistant and salt water resistant

**Cable Entrance Diameter:** 

0.547 inches

**Mating End Quantity:** 

4

**Contact Position Arrangement Style:** 

12-p single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

13.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

750.0 single mating end single contact grouping

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

0.0

Shell Type:

Solid

**Connector Locking Method:** 

Bayonet latch

**Connector Cable Strain Relief Method:** 

Cable clamp

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Terminal Type:** 

Crimp single mating end single contact grouping

**Shell Material:** 

Aluminum alloy

**Shell Surface Treatment:** 

Cadmium

**Shell Surface Treatment Specification:** 

Qq-p-416, type 2, cl 3 federal specification single treatment response

# NSN 5935-00-521-2388

Electrical Plug Connector - Page 2 of 2



### **Included Contact Quantity:**

12 single mating end single contact grouping

### **Included Contact Type:**

Round socket single mating end single contact grouping

#### **Special Features:**

Contact designation 14-92

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A039b0