

View Online at <https://aerobasegroup.com/nsn/5935-00-521-2479>

Body Style:

Straight shape

Overall Length:

Between 1.315 inches and 1.335 inches

Overall Height:

Between 0.360 inches and 0.370 inches

Overall Width:

Between 0.195 inches and 0.215 inches

Unthreaded Mounting Hole Diameter:

0.092 inches

Distance Between Mounting Facility Centers:

Between 1.114 inches and 1.129 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

31 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

900.0 single mating end single contact grouping

Polarization Method:

Mating end

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204 cl 1, type 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Included Contact Quantity:

31 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

24.000 in. Lg white wire leads

Precious Material And Location:

Contact surfaces gold and lead wire surfaces silver

Precious Material And Weight:

0.031 gold grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.