Electrical Plug Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-00-523-9460



Thread Class:

2b

**Thread Direction:** 

Right-hand

# Body Style:

Straight shape, internal coupling

## **Overall Length:**

1.406 inches

#### **Overall Diameter:**

2.250 inches

## **Environmental Protection:**

Watertight

**Threaded Device Type:** 

Coupling facility

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

28-11 single mating end

## **Contact Removability:**

Nonremovable single mating end all contact groupings

## **Contact Maximum Current Rating In Amps:**

41.0 single mating end 1st contact grouping

## Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end all contact groupings

## Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end all contact groupings

#### **Polarization Method:**

Key, multiple key groove

## Insert Position In Deg:

110.0

## Shell Type:

Solid

# **Connector Locking Method:**

Internally threaded coupling nut

# Thready Qty Per Inch (tpi):

18

## Thread Size:

1.750 inches

#### **Terminal Location:**

Back single mating end all contact groupings

## **Contact Surface Treatment:**

Gold single mating end all contact groupings and nickel single mating end all contact groupings

# NSN 5935-00-523-9460

Electrical Plug Connector - Page 2 of 2



Insert Material:	
Plastic single mating	lend
Contact Surface Tr	eatment Specification:
Mil-g-45204, type 1,	grade b military specification 1st treatment response single mating end all contact groupings and qq-n-290, cl 1, grade
federal specification	2nd treatment response single mating end all contact groupings
Terminal Type:	
Solder well single ma	ating end all contact groupings
Shell Material:	
Aluminum alloy	
Shell Surface Treat	ment:
Cadmium	
Shell Surface Treat	ment Specification:
Qq-p-416, type 2, cl	3 federal specification single treatment response
Included Contact Q	luantity:
4 single mating end	1st contact grouping
Included Contact T	ype:
Round pin single ma	ting end all contact groupings
Precious Material A	And Location:
Contact surfaces gol	ld
Precious Material A	And Weight:
0.028 gold grains, tr	оу
Precious Material:	
Gold	
Thread Series Desi	gnator:
Uns	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military Sta	andard):
Mil-g-45204 spec.	