AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-00-524-2277

Body Style:

Straight shape

Overall Length:

Between 3.340 inches and 3.360 inches

Overall Height:

0.715 inches

Overall Width:

Between 0.240 inches and 0.260 inches

Unthreaded Mounting Hole Diameter:

Between 0.110 inches and 0.130 inches

Distance Between Mounting Facility Centers:

Between 3.090 inches and 3.110 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end or plastic phenolic single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-p-19833 military specification single material response single mating end or mil-m-14 military specification single material response single mating end

Included Contact Quantity:

50 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping



Special Features:

Left side d-shaped socket guide rotated 180 deg, right side d-shaped socket guide rotated 180 degrees clockwise from normal

Precious Material And Location: Contact surfaces gold **Precious Material And Weight:** 0.050 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.