

View Online at <https://aerobasegroup.com/nsn/5935-00-524-5706>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Pcb, angle shape, external coupling

**Overall Length:**

0.530 inches

**Overall Height:**

0.583 inches

**Overall Width:**

0.250 inches

**Environmental Protection:**

Corrosion resistant and oil resistant and shock resistant

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Gk-c1 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

2.0 single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Thready Qty Per Inch (tpi):**

36

**Thread Size:**

0.250 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Beryllium and copper single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic tetrafluoroethylene single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204b type i grade a military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Pin single mating end single contact grouping

**Contact Material Specification:**

Mil-c-6941 military specification single material response single mating end single contact grouping

**Shell Material:**

Metal

**Shell Material Specification:**

Qq-s-764, class 303, cond a federal specification single material response

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial socket single mating end single contact grouping

**Color:**

Natural

**Precious Material And Location:**

Contact surface gold

**Precious Material And Weight:**

0.005 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Uns

**Fsc Application Data (non-core):**

Connectors, electrical

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-c-6941 spec.