# NSN 5935-00-525-3602

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-525-3602

## Body Style:

Angle shape, internal coupling

#### **Overall Length:**

Between 1.771 inches and 1.927 inches

## **Overall Height:**

1.304 inches

#### **Overall Diameter:**

1.141 inches

## Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

14-15 single mating end

#### Contact Removability:

Removable single mating end all contact groupings

#### **Contact Maximum Current Rating In Amps:**

7.5 single mating end 2nd contact grouping

#### **Polarization Method:**

Key, multiple key groove

## Insert Position In Deg:

0.0

#### Shell Type:

Potting

#### **Connector Locking Method:**

Spring friction

#### **Connector Cable Strain Relief Method:**

Potting type

#### **Terminal Location:**

Back single mating end all contact groupings

#### **Contact Material:**

Copper alloy single mating end all contact groupings

# **Contact Surface Treatment:**

Gold single mating end all contact groupings and silver single mating end all contact groupings

## **Insert Material:**

Rubber single mating end

# **Terminal Type:**

Crimp single mating end all contact groupings

# Shell Material:

Aluminum alloy

# Shell Surface Treatment:

Cadmium and chromate

# Shell Material Specification:

Qq-a-200/8 federal specification single material response

# NSN 5935-00-525-3602

Electrical Plug Connector - Page 2 of 2



**Insert Material Specification:** Mil-r-3065 military specification single material response single mating end **Included Contact Quantity:** 14 single mating end 2nd contact grouping Included Contact Type: Round socket single mating end all contact groupings **Special Features:** Potting boot 75 degrees angle **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.015 gold grains, troy and 0.015 silver grains, troy **Precious Material:** Gold and silver Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard):

Mil-r-3065 spec.