Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-528-6999

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Angle shape, pcb, external coupling
Overall Length:
0.583 inches
Overall Height:
0.530 inches
Overall Width:
0.250 inches
Environmental Protection:
Corrosion resistant and shock resistant and thermal shock resistant and moisture resistant
Distance From Mounting Shoulder To Front Face:
0.458 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
Osm single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Operating Tempurature Rating:
Between -65.0 degrees celsius and 105.0 degrees celsius
Thready Qty Per Inch (tpi):
36
Thread Size:
0.250 inches
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping

NSN 5935-00-528-6999

Electrical Receptacle Connector - Page 2 of 2



Insert Material	
	afluoroethylene single mating end
Contact Surfac	ce Treatment Specification:
	type 1, cl 2, grade c military specification single treatment response single mating end single contact groupin
Terminal Type	
Printed circuit s	ingle mating end single contact grouping
Contact Materi	al Specification:
Qq-c-530 federa	al specification single material response single mating end single contact grouping
Shell Material:	
Stainless steel	
Shell Material	Specification:
Qq-s-763, type	303 federal specification single material response
Insert Material	Specification:
Mil-p-19468 mil	itary specification single material response single mating end
Included Conta	act Quantity:
1 single mating	end single contact grouping
Included Conta	act Type:
Coaxial socket	single mating end single contact grouping
Precious Mate	rial And Location:
Contact surface	es gold
Precious Mate	rial And Weight:
0.005 gold grair	ns, troy
Precious Mate	rial:
Gold	
Thread Series	Designator:
Uns	
Shelf Life:	
N/a	
Unit Of Measu	re:
Demilitarizatio	n:
No	
Fiig:	
A039b0	
Mil-std (militar	y Standard):
Mil-g-45204b sp	Dec.