1



View Online at https://aerobasegroup.com/nsn/5935-00-528-7959

Body Style: Straight shape **Overall Length:** Between 3.215 inches and 3.225 inches **Overall Height:** Between 0.995 inches and 1.005 inches **Unthreaded Mounting Hole Diameter:** Between 0.120 inches and 0.130 inches **Distance Between Mounting Facility Centers:** Between 2.872 inches and 2.878 inches Mating End Quantity: **Contact Position Arrangement Style:** 24 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Contact to contact polarizing keys Shell Type: Solid **Connector Locking Method:** Lever-pin **Terminal Location:** Back single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and copper single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Tab, solder lug single mating end single contact grouping **Shell Material:** Copper alloy **Shell Surface Treatment:** Nickel **Insert Material Specification:** Mil-m-14, ty mdg military specification single material response single mating end **Included Contact Quantity:** 24 single mating end single contact grouping **Included Contact Type:** Leaf spring single mating end single contact grouping



Special Features:

Polarization key position a and d

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.024 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.