

View Online at <https://aerobasegroup.com/nsn/5935-00-528-8921>

Body Style:

Straight shape

Overall Length:

Between 1.165 inches and 1.185 inches

Overall Height:

Between 0.360 inches and 0.370 inches

Overall Width:

Between 0.195 inches and 0.215 inches

Environmental Protection:

Explosion proof and moisture resistant and shock resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.092 inches

Distance Between Mounting Facility Centers:

Between 0.960 inches and 0.975 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

25 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Glass single mating end and plastic polyamide single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1 military specification single treatment response single mating end single contact grouping

Included Contact Quantity:

25 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Special Features:

24.000 in. Lg green wire leads

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.025 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.