## NSN 5935-00-528-9364

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-528-9364

**Body Style:** 

Angle shape, pcb type

**Overall Length:** 

3.350 inches

**Overall Height:** 

0.359 inches

**Overall Width:** 

0.550 inches

#### **Environmental Protection:**

Cold resistant and heat resistant and vibration resistant and shock resistant and salt water resistant and humidity resistant and thermal shock resistant

#### **Unthreaded Mounting Hole Diameter:**

0.120 inches

#### **Distance Between Mounting Facility Centers:**

3.100 inches

## **Mating End Quantity:**

1

## **Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

#### **Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

#### **Polarization Method:**

Guide pin/socket

## **Connector Locking Method:**

Friction

#### **Operating Tempurature Rating:**

Between -55.0 degrees celsius and 125.0 degrees celsius

#### **Terminal Location:**

Side single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping

## **Insert Material:**

Plastic polyphenylene single mating end

## **Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

#### **Terminal Type:**

Printed circuit single mating end single contact grouping

### **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

# NSN 5935-00-528-9364

Electrical Receptacle Connector - Page 2 of 2



## **Guide Design And Location:**

D shape socket right-hand bottom at 6 oclock

## **Insert Material Specification:**

Mil-m-24519 military specification single material response single mating end

## **Included Contact Quantity:**

50 single mating end single contact grouping

## **Included Contact Type:**

Round pin single mating end single contact grouping

## **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.050 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.