

View Online at <https://aerobasegroup.com/nsn/5935-00-528-9371>

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

1.500 inches

**Overall Diameter:**

0.593 inches

**Environmental Protection:**

Shock resistant and vibration resistant

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Bnc single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

500.0 single mating end single contact grouping

**Contact Maximum Frequency Rating:**

4000.0 megahertz single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**Connector Cable Strain Relief Method:**

Crimp type

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Terminal Location:**

Back single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, class 2 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.005 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-c-39012 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-c-39012/17 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.