## NSN 5935-00-528-9755

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-528-9755

**Body Style:** 

Straight shape

**Overall Length:** 

Between 3.340 inches and 3.360 inches

**Overall Height:** 

0.715 inches

Overall Width:

Between 0.240 inches and 0.260 inches

**Unthreaded Mounting Hole Diameter:** 

Between 0.110 inches and 0.130 inches

**Distance Between Mounting Facility Centers:** 

Between 3.090 inches and 3.110 inches

**Mating End Quantity:** 

1

#### **Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

#### **Contact Removability:**

Removable single mating end single contact grouping

### **Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

## **Polarization Method:**

Guide pin/socket

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping

#### **Insert Material:**

Plastic diallyl phthalate single mating end or plastic phenolic single mating end

## **Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

#### **Terminal Type:**

Crimp single mating end single contact grouping

#### **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

## **Insert Material Specification:**

Mil-p-19833 military specification 1st material response single mating end or mil-m-14f military specification 1st material response single mating end or mil-m-14f military specification 2nd material response single mating end

#### **Included Contact Quantity:**

50 single mating end single contact grouping

## **Included Contact Type:**

Round socket single mating end single contact grouping

# NSN 5935-00-528-9755

Electrical Receptacle Connector - Page 2 of 2



Special	Features:
---------	-----------

Left side d-shaped socket guide rotated 180 degrees clockwise from normal, right side d-shaped pin guide normal

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.050 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.