Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-528-9990

| · · · · · · · · · · · · · · · · · · · |
|---|
| Thread Class: |
| 2a and 2b and 2a |
| Thread Direction: |
| Right-hand and right-hand and right-hand |
| Body Style: |
| Straight shape |
| Overall Length: |
| 1.250 inches |
| Overall Height: |
| 0.797 inches |
| Overall Width: |
| 0.438 inches |
| Environmental Protection: |
| Moisture resistant and salt water resistant and vibration resistant |
| Distance Between Mounting Facility Centers: |
| 0.937 inches |
| Threaded Device Type: |
| Coupling facility and mounting stud |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 14 single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 13.0 single mating end single contact grouping |
| Contact Maximum Ac Voltage Rating In Volts: |
| 500.0 single mating end single contact grouping |
| Contact Maximum Dc Voltage Rating In Volts: |
| 700.0 single mating end single contact grouping |
| Polarization Method: |
| Jackscrew |
| Connector Locking Method: |
| Jackscrew-socket |
| Thready Qty Per Inch (tpi): |
| 32 and 32 and 40 |
| Thread Size: |
| 0.138 inches and 0.138 inches and 0.112 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Conner allow single moting and single contact grouping |

Copper alloy single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment: Gold single mating end single contact grouping and copper single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Solder well single mating end single contact grouping **Contact Material Specification:** Qq-b-750 federal specification single material response single mating end single contact grouping **Insert Material Specification:** Mil-m-14, type sdg-f military specification single material response single mating end **Included Contact Quantity:** 14 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.014 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc and unc and unc Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-m-14 spec.